



I'm not robot



I am not robot!

Install over: interior concrete, terrazzo, ceramic and quarry tile, epoxy coating systems and non-water soluble adhesive residues on concrete ARDEX V™ Choose The Workhorse™ ARDEX V™ is the trusted leveler for big jobs on tight schedules. ic polymers. Install over: interior concrete, terrazzo, ceramic and quarry tile, epoxy coating systems and non-water ARDEX V™ Self-Leveling Underlayment. ARDEX MCTM RAPID One-Coat Moisture Control System. A Self-Leveling Underlayment that Consists of a Blend of Portland Cements, Other Hydraulic Cements and Polymers for Interior ARDEX V must be installed at a minimum thickness of 1/8" (3 mm) over the highest point in the floor, which typically results in an average thickness of 1/4" (6 mm) ARDEX MCTM RAPID WITH ARDEX V™ SELF-LEVELING UNDERLAYMENT. Use to level and smooth interior concrete, terrazzo and ceramic tile substrates, as well as non-water soluble adhesive residue on concrete, prior to the installation of finished flooring on, above or. Pourable or pumpable when mixe PARTGENERAL. SECTION installing ARDEX V, this filling is not intended to act as a repair method that will eliminate the possibility of joints and cracks telegraphing. ARDEX FEATHER FINISH, ARDEX Underlayment HC™ High-Capacity Self-Leveling, HC R™ High-Capacity Rapid Self-Leveling Underlayment, ARDEX V™ Self-Leveling Underlayment and Microsoft WordV TDS English ARDEX V™. Self-Leveling Underlayment. below grade. This Section includes a self-leveling underlayment that consists of a blend of Portland cements, other hydraulic cements and polymers that is used to level and smooth interior concrete, terrazzo, well-bonded ceramic & quarry tile, epoxy coating systems and properly prepared, non-water-soluble adhesive residue on concrete prior ARDEX V™ is a blend of Portland cements, other hydraulic cements and polymers that is used to level and smooth interior concrete, terrazzo, ceramic and quarry This Section includes a single-coat, fast-curing, % solids epoxy moisture management system formulated to suppress excessive moisture vapor emissions in new or existing concrete prior to installing an ARDEX Underlayment and flooring. Install moisture-insensitive tile and stone afterhours, most other floor coverings afterhours. Installs up to 2" (mm) in most applications. Levels and smooths a variety of interior substrates. ARDEX PTM Ultra Prime ARDEX V™ or ARDEX K® Self-Leveling Underlayment; Manufactured by ARDEX Engineered Cements Ardex Park Drive, Aliquippa, PA USA,, Contact Mike Tracy ARDEX V™ is the trusted leveler for big jobs on tight schedules. Installs up to 1/4" Ardex V Tech Data Sheet Cartwright Distributing Inc ARDEX V™. Self-Leveling Underlayment. Install over: interior concrete, terrazzo, ceramic and quarry tile, epoxy coating systems and non-water soluble adhesive residues on concrete Key Features Pourable with the ROVER® Rolling Barrel Cart; ARDEX V™. Self-Leveling Underlayment. ARDEX V™. Self-Leveling Underlayment ARDEX V™ is the trusted leveler for big jobs on tight schedules. Levels and smooths a variety of interior substrates. Pourable or pumpable. One-Coat Moisture Control System for Concrete to Receive ARDEX Products. Description And Usage. Walkable into hours.