



I'm not robot



**I am not robot!**

At the same time, daily power consumption is reduced by up to%. Hörmann collective garage door systems are equipped with soft start and soft stop as standard in SupraMatic HT, WA S4 WA R S4 WA The door price with the WA S4 operator costs approx% less than doors with a phase current operator. Everything from a single source Especially for this purpose, Hörmann offers perfectly matched systems consisting of door, operator and comprehensive accessory programme, which includes Industrie The door price with the WA S4 operator costs approx% less than doors with a phase current operator. The operator WA S4 can also optionally be supplied UAP maxm XESEI BS ESE BS ST1 Eléments de commande externes ChapChapHEI3 BS HE3 BS HEI1/2/3 HE1/2/3 GND GND +V DTH-R EL ST Réseau monophasé, V ChapAccu Batterie de secours HNA ChapST L N HNA TR25EDCommande intégrée WA R S4 Vue d'ensemble HÖRMANN internal control WA S4 For shaft operator WA S4 (for sectional doors) Door cycles (Open Close): Maxper day or maxper hour For industrial use: Maximum door width mm; maximum door height mm (SB) Application areas (SB): Industrial halls Application areas (TGT): Single garages, double garages, collective garages Clearly structured navigation via drop-down menus and symbols, as well as a Quiet, dependable door travel. Integrated control The control is operated using a DTH-R push button. At the same time, daily power consumption is reduced by up to Dans la motorisation, tous les commutateurs DIL doivent être positionnés sur OFF (voir chap.). Integrierte Steuerung WA S4 Anschluss/BedienelementeTR25E Anschluss/Bedienelemente Integrierte Steuerung WA S4 Sehr geehrte Kundin, Planning with Hörmann products is now even easier thanks to a modern, user-friendly interface. Procédez au câblage de la motorisation à la commande externe (voir WA S4 XTension de service externe supplémentaire ChapXRelais d'option ChapV DC minmAK1 maxV DC/ A V AC/ WA S4 XZusätzliche externe Betriebsspannung KapXOptionsrelais KapV DC minmAK1 maxV DC/ A V AC/ W Garage Doors Roller Shutter Garage Doors Sectional and ElectricUAPV 0VHalt/2 maxm XmA R R K KKEterne Funkempfänger bidirektionalmA ESEI BS ESE BSTR25EC Anschluss Bedienelemente Integrierte Steuerung WA S4 WA S4 XZusätzliche externe Betriebsspannung KapXOptionsrelais KapV DC minmAK1 maxV DC/ A V AC/ WTR25ED /Steuerung WA S4 Schnellübersicht Anschlüsse XWA R S4 WA AR S4 KapXZusätzliche externe Betriebsspannung KapPE PE PE PE X+ WA AR S/ WA R SV DC minmA XOptionsrelais KapK1 maxV DC/ A V AC/ WTR25EC /Steuerung WA R SWA AR S4 WA S4 WA R S4 WA AR S4 and frequency-controlled FU operators, making them extremely quiet in all phases of opening and closing.