



I'm not robot



I'm not robot!

Connector to controller display cable outlet connector display cable coupling connector. there are multiple items displayed on s886 as follows: battery level. ■ for electric scooter only ■ 1. button introduction ■. doc), pdf file (. 17: cruise options: not available so set to 0. 2: power assist + electric drive – electric drive does not work in direct start mode. page 38 connecting the av controller— continued making hdmi connections step 1: use hdmi cables to connect the av controller' s hdmi jacks to your hdmi- compatible blu- ray player/ dvd player, tv, projector, and so on. throttle damaged or out of operation.

■■ appearance size and material. view online or download sciwil s886- lcd user manual. page 4: safety notes changzhou sciwil e- mobility technology co. pdf), text file (. p15: controller under voltage value. summary of contents for fm s- 886. ■■ working voltage and. i have a brainpower controller that i am trying to fit to my bike at the moment. p16: odometer zero out. throttle failure. s886- lcd bicycle accessories pdf manual download.

ride66 s866 control panel instructions user' s manuall download. 2 when it is power- on state, long press θbutton to close, and short press i button to adjust the power gear. instrument front view instrument side view. step 2: assign each hdmi in to an input selector. 1: electric drive (throttle) only – the vehicle is driven by the handlebar. lcd s886 instructions - free download as word doc (. thread starterseed ric. try to unplug and replug all the connections and checking that there are no bent pins. 5vehicle status display area. 1 when it is power- off state, long press θbutton to start; after start, short press θbutton, interface will switch in odo ■ trip ■ vol ■ tm ■ err.

2 control and setting items power switch, light. scribd is the world' s largest social reading and publishing site. exterior parameters casing material: abs display material: high hardness acrylic (the same hardness value as tempered glass). 0 - free download as pdf file (. see “ video input setup” on page 50. a s886 controller manual pdf long 5 second press of the top power button will reset the odometer. 1 chuangxin dadao, xinbei district, changzhou, 213031, jiangsu, china. key pad position: there are 3 keys on s886 display.

p13: power magnetic steel disk type setting 5 ■ 8 ■ 12grain magnetic steel type; p14: set the current limit of the controller, default: 12a, range: 1- 20a; p15: controller under- voltage value; p16: odo reset, long press the button to clear odo for 5 seconds ■ technical (batteries, motors & electrics) technical general discussion. s866 bike controller manual. communication reception failure. contact ■ jackie yan. 2display interface 1. manual for s886 controller. e- bike lcd s886 instructions. txt) or read online for free. if option available, the range s886 controller manual pdf is between; 0: no cruise. in this status the power gear does not work. long press keyboard, boot, enter the display. 3 long pressθ+ i button enter into mode setting. this manual will walk you through assembly, settings and operations of sciwil display products in easy steps, to facilitate operations on your e- bike. controller malfunction. my motor does not have a white wire running from it, only the red, black, green blue yellow. s866_ lcd- jun6v7 - free download as pdf file (. functional operation 1turn on and turn of long press keyboard, boot; long press key, shut down.

p12: assist power intensity range: 0- 5 p13: power magnet steel number: 5 / 8 / 12pcs p14: current limit value: 12a by default; range: 1. by the controller. 5 functions and key pad. note: some products may use waterproof connectors, in which case the internal wire arrangements cannot be identified from

outside. ensure everything is properly connected. this stops the battery from running too low and being unable to charge.

in following introductions: is called " on/ off", is called " info", operations include short press, press and hold of a single key or two keys:. press and hold the up key for 5 seconds and odo distance will be cleared. 4 vehicle power gear adjustment, 0- 9 digital display and file bar display; 3. in this video we will explain about installing a pure sine wave controller and display for a electric scooter for more information and user manual this s886 d. when the vehicle stops driving and does not operate the instrument for 10 minutes, the instrument will automatically shut down and turn of the power supply of the electric vehicle. page 1 lcd display s- 886 user manual v. communications protocol: uart. the shell of the product is abs, and the transparent liquid crystal window is imported high- hardness acrylic, and the hardness value is equivalent to tempered glass. huashan road, changzhou, jiangsu, china fax: tel:. the lcd is marked as model lcd s866. we have 1 sciwil s886- lcd manual available for free pdf download:. (the time of a single hall period, unit: 1ms) the instrument will calculate the true speed based on the diameter of the wheel and the signal data(the number of magnetic steel needed by the motor hall) 3. contact your e- bike dealer or customer service. user manual s886_ protocol 2_ v1. email add no.