



I'm not robot



I am not robot!

IPdegree of protection. For variable speed driveslines message display capability. It weighs g. Environmental performance of the product This terminal is used to locate the Human-Machine Interface of the Altivar drive remotely on the door of an enclosure. For variable speed driveslines message display capability. Environmental performance of the product The Altivar drive includeslogic inputs,analog inputs,analog output, andrelay outputs (withNO andNO/NC contacts). It provides a pixel resolution of x pixels. The Altivar drive includes an integrateddigit,segment LED display with abutton keypad and includes an RJModbus port plus a four-screw terminal block for BACnet, Modbus, Metasys N2 and Apogee P1 Product Data Sheet VW3A LCD GRAPHIC KEYPAD IP RATING ATV Technical Characteristics CategoryDiscount Schedule CP4C GTIN Package QuantityWeight lbs. The Altivar drive includes an integrateddigit,segment LED display with abutton keypad and includes an RJModbus port plus a four-screw terminal block for BACnet, Modbus, Metasys N2 and Apogee P1 remote graphic terminal, Altivar, x pixels, IP VW3A Product availability: StockNormally stocked in distribution facility. Product data sheet VW3A The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products VW3A remote graphic terminal, Altivar, x pixels, IPMain Range of product Altivar Range compatibility Altivar AltivarAltivar Liff AltivarAltivar Machine VW3A remote graphic terminalx pixelsIPMain Range of product Altivar Range compatibility Altivar AltivarAltivar Liff AltivarAltivar Machine ATV VW3A remote graphic terminalx pixelsIPPrice*GBP Main Range of product Altivar Range compatibility AltivarAltivarQ Altivar Altivar Altivar_VW3Apdf Characteristics. Its maximum operating temperature is°C. Free download Programmable option card, conforms with IEC– VW3A remote graphic terminalx pixelsIP€ Main Range of product Altivar Range compatibility Altivar AltivarAltivarAltivarAltivar Altivar VW3A remote graphic terminal, Altivar, x pixels, IPMain Range of product Altivar Range Compatibility Altivar AltivarAltivar Liff AltivarAltivar Machine remote graphic terminal, Altivar, x pixels, IP VW3A Product availability: StockNormally stocked in distribution facility. It is used to control, adjust and configure the drive, display the current values (motor, input/output values, etc The Altivar drive includeslogic inputs,analog inputs,analog output, andrelay outputs (withNO andNO/NC contacts). VW3A remote graphic terminal, Altivar, x pixels, IP Product availability: StockNormally stocked in It can be used with a direct connection or a Bluetooth® wireless connection. Returnability Y Country of Origin CN Shipping and Ordering Product data sheet. Wide range of operating temperature from °C to°C. Availability Code Stock Item: This item is normally stocked in our distribution facility. IPdegree of protection. Wide range of operating temperature from °C to°C.