



I'm not robot



I am not robot!

reduces c Merlin Gerin Masterpact, Interpact INS/IN and Compact C switch-disconnectors c current ratings to A for commercial applications and to A for industrial NSN UI V UIMP 8KV IR X63A IM A COMPACT MERLIN GERIN. circuit breaker Compact NSNTMDA poles 4d has not been replaced. Used MERLIN GERIN NSN Tested and cleaned months guarantee Dedicated courier The Masterpact NW range is designed for DC voltages from to V and offers and pole versions. These circuit A unique and small insulating casing for all five ratings (to A) simplifies layout design and installation. Utilisez une protection différentielle unique RCCB type B entre recepateur et alimentation. two high breaking-capacity levels N and H: N =kA for systems y V. H =kA for systems y V, H =kA for systems y V, H =kA for systems y V %PDF %â€œâ€šObj /Linearized/O/H [] /L/E/N/T >> endobj xref mmmmmmmmmmm A at °C. reverse feeding maintenance free breaker design. [Ui] rated insulation voltage V AC/Hz conforming to IEC [Uimp] rated impulse withstand voltage kV conforming to IEC [Ue] rated operational voltage V AC/Hz conforming to IEC V DC conforming to IEC Breaking capacity code (3) NSN et U u V: Ics =% Icu (4) operational voltage y V Compact circuit breakers NS Number of poles Control manual toggle b direct or extended rotary handle b electric b Connections fixed front connection b rear connection b plug-in (on base) front connection b rear connection b withdrawable (on chassis) front connection b %PDF %â€œâ€šObj /Linearized/O/H [] /L/E/N/T >> endobj xref mmmmmmmmmmm RCCBA type B. MERLIN GERIN. I RCCB D. NTEST MONTHLY. The new COMPACT NS line achieves a significant technical advance in the evolution of molded case circuit breakers. RCCB. three current ratings: A. Please contact your customer care centre for more g. pdf (3) NSN et U u V: Ics =% Icu (4) operational voltage y V Compact circuit breakers NS Number of poles Control manual toggle b direct or extended rotary circuit breaker Compact NSXH, kA at VAC, TMD trip unit A, poles 3d Coordination of motor feeder components Thanks to limitation, the harmful effects of short-circuits on a motor feeder are greatly reduced. Use only one type B RCCB's between the load and the power supply NSN UI V UIMP 8KV IR X63A IM A COMPACT MERLIN GERIN Used MERLIN GERIN NSN Tested and cleaned months guarantee Dedicated courier Delivery across Europe even in h TECHNICAL DATA MANUFACTURER MERLIN GERIN MODEL NSN CATEGORY Contactors WEIGHT [KG] HEIGHT [CM] LENGHT [CM] WIDTH [CM]/7 SUPPORT AVAILABLE GROUPE SCHNEIDER. Proper limitation of circuit-breakers NSJ and NSJ Circuit Breakers.