



I'm not robot



I am not robot!

Catalogue Data Sheet U6B AISI ABLACK. yPe h Recess) M. achlNe scRevs. Current norm: DIN EN ISO, Equivalent norms: ISO ; CSN ; PN ; UNI ; Send Inquiry. The DIN standard specifies the tolerances and the variation in form of phillips countersunk head screws, and covers metric thread diameters for sizes M up to and including M The DIN standard covers both pozi (type Z) and phillips (type H) drives Hetraco, DIN, DIN,, Verzonken schroef met kruisgleuf (Phillips/Pozidriv), Senkschraube Kreuzschlitz (Phillips/Pozidriv), Cross recessed countersunk head screw (Phillips/Pozidriv) Created Date 5/18/AMIN C I N C I N C I N C I N C I N C I N C I N C I N C T I STNS DIN & MACHINE SCREWS ISO Torx ® DIN° F. lat. d) For structural boltingN (for M12),N (for M14) andDIN All dimensions in mm DINCross recessed countersunk flat head screws. b) To calculate As,nom, see in ISO c) For fasteners with thread tolerance 6az in accordance with ISO subject to hot dip galvanizing, reduced values in ac-cordance with ISO, Annex A, apply. Current norm: DIN Missing: pdfDIN () ISOANSI B MDo Not Specify A Minimum I-bad Height The DIN standard specifies the tolerances and the variation in form of phillips countersunk head screws, and covers metric thread diameters for sizes M up to and I N C I N C I N C I N C I N C I N C I N C T I STNS DIN & MACHINE SCREWS ISO Torx ® DIN° F. lat. yPe h Recess) M. achlNe DIN CSK PHILLIPS Catalogue Data Sheet A2BSize→ Parameter↓ Mx M2x Mx M3x Mx M4x M5x M6x M8x M10x D (max) DIN CSK PHILLIPS. andard in a variety of materials and fin. DIN Nominal Data is strictly DIN CSK PHILLIPS (H) Catalogue Datasheet R1BMx M3x M4x M5x M6x M8x MaxMinDIN UDC DEUTSCHE NORMEN e DIN C B kecessed Countereunk (Flat) Head Screws (Countersunk Heada according to ISO) Sönkgchrauben mit Ereuzschlitz (Senkköpfe nach ISO) For connection with an ISO Recommendation in preparation, Bee Explanationg itch is specified. Metric DIN is a cross recessed (Phillips) flat countersunk machine screws. Metric machine screws are designed for metal to metal applications requiring a pre-drilled hole rows · DINCross recessed countersunk flat head screws. ate shipping from stock: Diameters ranging fromM to M10up tomm long in. P. hlllIPs (t. Buy DIN rs offers over unique fastener productsfrom stock in inch and metric. P. hlllIPs (t. Sizes in BLUE are non-prefered. Availability is limited and MOQ is higher. inc plated steel and stainless steel A2 and AView parts by clicking on the following link:DIN cross rece DIN () ISOANSI B MDo Not Specify A Minimum I-bad Heightoo For Machhe Screws, The Letter A After The DIN Number Indicates Full Thread Scope of the DIN Standard.