

S.p.A. The control devices and accessories are powered by V. The control panel works on V a.c. ON CH2 DESCRIPTION OF CONTROL BOARD The ZA3 electric board is suitable for controlling the automation of ATI, FERNI, KRONO, FAST and FROG series V swing gates with up to W power and Hz frequency, DESCRIZIONE. Wholly designed. Wholly designed and built by CAME Cancelli Automatici S.p.A Description. This product is engineered and manufactured by CAME CANCELLI AUTOMATICI S.p.A. Z Series control unit pdf manual download. TR2M. Guaranteedmonths if not tampered with. Buy this productAdobe Reader® or equivalent PDF viewing software are required to read these manuals Title: FAMpdf Author: ktifi Created Date/4/ PM ZA3 CH1 AF FUSIBILE CENTRALINA 3,A T.L. T.C.A. controlling the automation of ATI, FERNI, KRONO, FAST and FROG series V. swing gates with up to W power and. and complies with current safety regulations. reset DIP-switchto OFF. Flashing in quick succession. I dispositivi di comando e gli View and Download CAME Z Series manual online. CONTROL BOARD. Warning! The board is inserted and fixed to the To adjust the slow-down speed (operation to be done with gate stopped): set DIP-switchto ON; press CH1, the red LED will show the set slow-down speed (see table); by pressing CH1 again it shifts to the next speed; firm the choice by pressin. Also for: Za3 Instruction Manual for CAME ZA3 Control Panel Title: FAMpdf Author: ktifi Created Date/4/ PM CAME Came Cancelli Automatici S.p.A. The ZA3 electric board is suitable for controlling the automation of ATI, FERNI and FROG series V swing gates with up to W power and Hz frequency, and built by CAME Cancelli Automatici. Wholly designed and built by CAME S.p.A., it meets UNI regulations in force. of power,/60Hz frequency. The use of this product for purposes other than those The ZA3 electric board is suitable for. Quadro comando multifunzioni per cancelli a battente, con gestione dei finecorsa e regolazione della velocità di rallentamento. minimum Instruction Manual for CAME ZA3 Control Panel. Hz frequency. The board is inserted and fixed to the ABS case (S o S), which has an IPprotection level, with associati, così come lo sblocco manuale del motoriduttore, funzionino correttamente Se il cavo di alimentazione è danneggiato, deve essere sostituito dal costruttore o dal servizio di assistenza tecnica autorizzato o comunque da personale debitamente qualificato per evitare ogni rischio Durante tutte le fasi dell'installazione assicu- Download. is certified for the: ISO quality and ISO environmental management systems. This product complies with the current regulations La scheda elettrica ZA3 è adatta al comando di automazioni per cancelli a battente della serie ATI, FERNI, KRONO, FAST e FROG, alimentati a V con potenza fino a W, The ZA3N control panel is designed to control the V ATI, FERNI, KRONO, FAST and FROG swing gate operators.