



I'm not robot



I am not robot!

High°C. Search for products that fit your needs with the DELFINGEN products guide°C. None. Read Download in PDF Americas region. Thick Fiberglass braid Thick Silicone coating Flame retardant & self extinguishing Standard color: brick red. Abrasion. Sound dampening Fiberglass. Renault Trucks Delfingen Industry iFRANCE Tél: +(0)Fax: +(0)email: delfingen@ Europe & South America: Delfingen FR-RoissyPlace de Londres, Bât. Saturne BPParis Roissy CDGFRANCE Tél: +(0)North and Central America: Delfingen US, Inc DE CL ARATI O N O F CO M P L I ANCE. High temperature silicone rubber. Application & Material. None. NU-GUARD As a global leading company in wiring harness protection, Delfingen offers a large range of convoluted tubes and dedicated accessories to protect, route and fasten your cable NU-GUARD SC-P is particularly suited to protect and bundle wire harnesses, cable assemblies and hoses from cutting, abrasion and chafing. < mm. Flammability. The flat knit construction of the NU GUARD SC P is made of PET monofilament and textured multifilament combination; which gives a lightweight, rugged Europe region. Thermal effectiveness. glass -SLEEVE AG has excellent electrical, chemical and oil resistance properties, excellent heat stability and flexibility for ease of push Hose & wire heavy duty protection. Nu-Guard SC-P is particularly suited to protect and bundle wire harnesses, cable assemblies and hoses from cutting, abrasion and chafing. Dear valued customer, By virtue of the statement of chemical compositions of the raw materials established by our suppliers, we confirm, honestly, that the products supplied by DELFINGEN related to the products listed in ANNEX do not contain dangerous substances at or above the following thresholds Delfingen Industry iFRANCE Tel: +(0)Fax: +(0)delfingen@ Europe, Africa & South America: Delfingen FR-RoissyPlace de Londres, Bât. Saturne BPParis Roissy CDGFRANCE Tel: +(0)sales-eaas@ North & Central America NU-SLEEVEAGNU-SLEEVE AG is a coated fiberglass sleeving made by applying a proprietary blend of acrylic polymers to a closely woven electrical grade fibre. Low°C. Read Download in PDF. Contact-us! Heavy duty thermal insulation °C forminutes °C forminutes. NU-GUARD SC-P is selfNU-SLEEVE AG is used extensively in consumer appliances, lighting fixtures, stove, oven and furnace controls as well as relays, breaker panels, switchgear and other DELFINGEN_NU-GUARD SC2-P industrial_EN_v Physical properties Spec Value Operating temperature/°C (°F) Peak temperature°C (°F) Physical properties Spec Value Operating temperature/°C (°F) Peak temperature°C (°F) Abrasion resistance SAE ARP A >cycles NU-GUARD SC-P.