



I'm not robot



I am not robot!

Selection of connections for heated hoses and application heads. Modular design for flexibility and reduced costs. Easy operation and maintenance. Easy installation and integration. to ISO Class Electronics ICS-Net Robatech Concept hot melt unit. Easy integration Concept B is suitable for melting and processing thermoplastic hot melt adhesives. The melters are easy to install Proven reliability in all industries – low maintenance cost, low life cycle cost. Thanks to the modular design with different tank sizes, pumps and optional components, a variety of applications can be supported. Product SKU: ROCNCPT Optional a ICS TRM glue pattern controller can be built in, against an extra price of euro Concept-B Free download as PDF File.pdf, Text File.txt) or read online for free. Folleto concept b Robatech concept Feeder Sold Year Technical characteristic litre tank capacity Filling of the reservoir x mm Power of fusion kg/h Number of pump extrusion or 2 Areas of external heating (hoses/heads of application) 4, 8, or Operating temperature ° C Power supply V/Hz 3 LNPE Absorbed power KW 20 Simple to learn and to Missing: pdf Concept-B Free download as PDF File.pdf, Text File.txt) or read online for g: robatech concept hot melt applicator with tank sold Year: DESCRIPTION: Robatech offer a comprehensive range of tank melters to handle all types of EVA, PSA and APO Missing: pdf CONCEPT STREAM. The system can be extended at all times. Термоклеевые аппараты Эффективность быстрый разогрев безопасность. Modular, extendable and backwards-compatible with Robatech systems. Concept B is available with manual and automatic filling, is energy-optimized Filling Manual or automatic (RobaFeed 3) Number of pumps or or or Pump type Piston, Gear or Gerotor pumps Supply voltage to V, LNPE Electrical power kW kW kW kW kW Compressed air supply bar, dry, not oiled acc. Thanks to the modular design with different tank sizes, pumps and optional components, a ADVANTAGES OF THE CONCEPT SERIES – AT A GLANCE. Energy-efficient and safe thanks to CoolTouch insulation. СОВРЕМЕННЫЙ СПОСОБ ПЛАВЛЕНИЯ КЛЕЯ. Without Robatech's written approval it is not permitted to copy and distribute this manual or parts thereof in any form whatsoever, or to transmit it by means of electronic systems Concept Diamond is available with manual and automatic filling, is energy-optimized and safe in its operation. Компактность и Concept Product description The operating manual The information contained in this operating manual refers to: All «Concept» hot melt applicators of Robatech from Concept C is suitable for melting and processing thermoplastic hot melt adhesives.