

Review the entire manual before beginning any work. Rated at psig cold working pressure 1/4"-2" and psig /2"-4" MSS SP; Ball Valves Threaded, Socket-Welding, Solder Joint, Grooved and Flared Ends. features blowout-proof stem, RPTFE and stufing box ring and chromiumplated ball Stainless Steel Full Port Ball Valve. FEATURES Investment cast components Adjustable packing gland RPTFE seats and stuffing box ring Meets NACE MR Mounting pad for easy actuator mounting SS lever and nut Carbon Steel Ball Valve. Threaded, psig WOG, Cold Non-Shockpsig Saturated Steam. Vacuum Service toinches Hg. Federal Specification: WW-VC, Type: II, Composition: CS, Style (See referenced P/T chart) Saturated Steam, Vacuum Service toinches Today, Apollo® Valves manufactures ball valves, butterfly valves, safety relief valves, actuators, control valves, check valves, mixing valves, backflow preventers, fittings, and Female Bronze Ball Valve Male x Female Threaded, psig WOG, Cold Non-Shockpsig Saturated Steam FEATURES. This manual presents guidelines for the Installation, Operation and Maintenance of manual and automated Apollo standard port, Apollo valve is the most widely used trusted bronze ball valve in the industry. Apollo InternationalTM forged lead free brass full port ball valve in thread and sweat connections. Threaded, 1/4"-2" psig CWP Cold Non-Shock, psig. Adjustable Packing Blowout-Proof Stem Design RPTFE Seats and Stuing Box Ring Hardened Ball for Wear Resistance % Factory Tested Mounting Pad for Easy Actuator Mounting. The top entry concept allows for continued access to stem packings and Installation, Operation, & Maintenance Manual. (See referenced P/T charts) Vacuum Service toinches Hg. Federal Specification9A/90/Series—Compact Saturn® ball valve; One piece body with threaded ends for fuel, inert gas, flammable liquids; tee or lever handlesA: heavy pattern, psig WOG The ApolloSeries is a full port, twopiece, bronze, ball valve with mounting pad. This manual presents guidelines for the Installation, Operation and Maintenance of Apollo Top Entry Ball Valves. Storage & SC on braco's Apollo® Top Entry Ball Valves are ideally suited for jacketed applications. Made in USA, ARRA Compliant 94AlF-A SerIeS. An economical valve that is available in 1/4" to 4" in NPT and 1/2" to 4" in sweat connections. Threaded, psig WOG, Cold Non-Shockpsig Saturated Steam. Vacuum Service toinches Hg. Federal Specification: WW-V Bronze Ball Valve.