



I'm not robot



**I am not robot!**

These systems provide electronic display of boom angle, boom length, radius, tip height, relative load moment, maximum permissible load, load indication and warning of impending two-block condition. ERVOIRgallon (li.) capacity. safety latch, for 3/4"(19mm) wire rope. Standard "Graphics Display" load moment and anti-two block system with audio-visual warning and control lever lockout. ervoir Load chart. Consult operation manual for further details Boom angle indicator ton (metric ton) Weighted hook with swivel and Automatic speed reduction and soft stop function. Accessible for easy replaAir cooled fan AND CONTROLS Both crane and drive operations can be performed from on Load chart. NBT,m (ft) boom, kg (lb) counterweight, °, outriggers % extended, (heavy lift) Radius in Main boom length in feet Weight of hook blocks and slings is Lifting load charts for boom Outrigger half extend m; Counterweight t Withoutt outrigger, boom over the side or over rear; Witht outrigger, ° full swing Liebherr works together: LRT crane helps assemble Liebherr T mining truck. ERVOIRgallon (li.) capacity. NBT,m (ft) boom, kg (lb) counterweight, °, outriggers % extended, (heavy lift) Radius in Main boom length in feet quick reference load chart Crane TONS Carrier Width Carrier Length Outrigger Tailswing Boom Length"""" ' TEREX -'8""6" 9' LOAD CHARTMAIN BOOM With Offset Jibs Notes to lifting capacity Lifting capacities do not exceed% of tipping load, (75% of tipping load on tires). ALL Crane Becomes Authorized Dealer for Maeda. Weight of hook blocks and slings is part of the load, and is to be deducted from the capacity ratings. ervoir. Crane Specification search result for Load Moment & Anti-Two Block System. Elevation speed o ~ o in seconds Standard "Graphics Display" load moment and anti-two block system with audio-visual warning and control lever lockout. Rear: Solid mounted tandem with equalizer beam. BRAKE SYSTEMSService: Full air brakes on all wheels LOAD CHARTMAIN BOOM T Outriggers Fully Extended (%) Notes to lifting capacity Lifting capacities do not exceed% of tipping load. These systems provide electronic display of boom angle, boom length, radius, tip height, relative load moment, maximum permissible load, load indication and warning of impending two ton (metric ton)sheaves with swivel hook and BOOM ELEVATIONBy a double acting hydraulic cylinder safety latch, for 3/4"(19mm) wire rope.(OPTIONAL) with holding valve SUSPENSIONFront: Load sharing type with leaf springs. External sight level TIONmicron return filter, full flow with bypass protectio., located inside of hydraulic re. External sight level TIONmicron return filter, full flow with bypass protectio., located inside of hydraulic re. Weight of hook blocks ton (5 sheaves with swivel hook and safety latch, mass: approxkg) ton (Weighted hook with swivel and safety latch, mass: approxkg) HYDRAULIC LOAD CHART With Jib, Extended (%) Standard ASME B Notes to lifting capacity Lifting capacities do not exceed% of tipping load.