

Achieves the full opening width of mm for all leaf heights. Largeur du vantail a. Outward-opening top-hung windows with a reveal depth of mm Uniquement pour fenêtres rectangulaires montées. Little space necessary thanks to flat design of the scissors. AREAS OF APPLICATION pákové otevírače okenotevírač nadsvětlíků pro pravoúhlá okna se zdvihem otevření mnějírka křídla (min.) mm, výška křídla (min.) mm, hmotnost křídla (max.) Surface-mounted fanlight opener with an opening width of mmOLN. We provide extensive support for your building demands and realise solutions that unite functionality, safety, comfort and design OLN top-hung outward-opening AREAS OF APPLICATION Convenient daily ventilation for rooms and staircases Outward-opening top-hung windows with a reveal depth of mm Automation by E electric linear drive Installation on wooden, plastic or aluminium windows Leaf installation Surface-mounted fanlight opener with an opening width of mm Convenient daily ventilation for rooms and staircases. Unhinging inhibitor and lockable hand lever offer additional safety GEZE counts among the best worldwide for products, systems and services related to door, window and safety technology, and automatic doors. Integrated leaf The GEZE slimline fanlight openers OLN and OLfulfil the extensive requirements of the RAL quality protection targets and the high RAL quality level. Installation on wooden, plastic or aluminium windows. The opening width can be adjusted. Slimline fanlight opener with a large Domaine d'application. Integrated leaf locking mechanism in the scissors ensures secure locking, corner Achieves the full opening width of mm for all leaf heights. AREAS OF APPLICATION The GEZE slimline fanlight openers OLN and OLfulfil the extensive requirements of the RAL quality protection targets and the high RAL quality level. Surface-mounted slimline fanlight opener for rectangular windows, inward opening. Units: slimline scissor. Poids du vantailkg max. Little space necessary thanks to flat design of the scissors. Slimline fanlight OLN. Surface-mounted fanlight opener with an opening width of mm. The opening width can be adjusted, casement bracket. Poids de remplissage Surface-mounted fanlight opener with an opening width of mm Automation by E electric linear drive. back plate. Leaf installation OLN. Surface-mounted fanlight opener with an opening width of mm. verticalement avec ouvrant à soufflet ou à l'italienne, avec projection à l'intérieur, en bois, PVC ou métal, avec hauteurs de recouvrement deamm. scissor stay base. OLN top-hung outward-opening AREAS OF APPLICATION Convenient daily ventilation for rooms and staircases Outward-opening top-hung windows with a reveal OLN GEZE GmbH Reinhold-Vöster-Straße-D Leonberg TEL+ Mail @ TZ. Burglar Contents.