



I'm not robot



**I am not robot!**

It can be used on interior subfloors before the application of floor coverings. WHY IS SELF-LEVELING AN ADVANTAGE? Formulated for smoothing and levelling interior and exterior (with covering) residential and non-industrial subfloors before applying: Wood flooring. USES. Self-leveling cementitious compounds can quickly even out large floor surfaces and require minimal effort. It provides a reduced-shrinkage and smooth finish. WHY IS SELF-LEVELING AN ADVANTAGE? Reference Sikafloor® Level is suitable for filling, smoothing and levelling of suitable substrates before applying parquet, ceramic tiles, textile and elastic floor coverings. After the product is mixed with water, Sikafloor® Level is poured over the uneven substrate of the floor. Parquet flooring. Company name of supplier Use suitable Sikafloor® Level is suitable for filling, smoothing and levelling of suitable substrates before applying parquet, ceramic tiles, textile and elastic floor coverings. Self-leveling cementitious compounds can quickly even out large floor surfaces and require minimal effort. Use suitable Sika Primer according to absorbency and condition of substrate. Trade name: Sikafloor® Level. Relevant identified uses of the substance or mixture and uses advised against. Use suitable Skin and body protection: Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. After the product is mixed with water according to the product data sheet, it is poured over the uneven substrate of the floor. Parquet flooring. Company name of supplier Use suitable Sikafloor® Level is suitable for filling, smoothing and levelling of suitable substrates before applying parquet, ceramic tiles, textile and elastic floor coverings. Self-leveling cementitious compounds can quickly even out large floor surfaces and require minimal effort. Use suitable Sika Primer according to absorbency and condition of substrate. Trade name: Sikafloor® Level. Relevant identified uses of the substance or mixture and uses advised against. Product use: Levelling compound, Floor levelling compound. Details of the supplier of the safety data sheet. It provides a reduced shrinkage and smooth finish compound for interior and exterior subfloors. Ceramic tiles Sikafloor® Level is a high-build, polymer-modified cementitious floor levelling compound with very low VOC emissions. Product use: Levelling compound, Floor levelling Sikafloor® Level is suitable for filling, smoothing and levelling of suitable substrates before applying parquet, ceramic tiles, textile and elastic floor coverings. Product Data Sheet (PDS) PDFKB (en) Very low emission cement based self levelling compound suitable for interior and exterior areas. Sikafloor® Level is noted for its extremely low shrinkage. Sikafloor® Level (ZA) is suitable for filling, smoothing and levelling of suitable substrates before applying parquet, ceramic tiles, seamless resin floors, textile and elastic floor coverings for interior and exterior residential and non-industrial areas. Sikafloor® Level is suitable for filling, smoothing and levelling of suitable substrates before applying parquet, ceramic tiles, textile and elastic floor coverings. Sikafloor® Level is a high-build, polymer-modified cementitious floor levelling compound with very low VOC emissions.