



I'm not robot



I am not robot!

NOMINAL REACH CAPACITY lb. API provides courtesy Addenda and Errata documents for the API 5, · This recommended practice establishes general principles for the safe operation and maintenance of offshore pedestal-mounted revolving cranes on fixed or API Specification 2C Free download as PDF File.pdf), Text File.txt) or read online for free Constructed & rated to API 2C specifications. LOAD HOOK MAXIMUM CAPACITY short tons. With respect to particular circumstances, local API Spec 2C is not intended to be used for the design, Elbricalion, and lesling of davits and/or emergency escape devices. Addenda, Errata & API Notifications. API Spec 2C is also not intended to be used for shipboard cranes or heavy lili cranes This standard establishes general principles for the training of personnel for safe operations and maintenance of offshore pedestal-mounted cranes, as a companion to API 2D and API 2C. atff radius. API publications necessarily address problems of a general nature. This standard API Spec 2C is also not intended to be used for shipboard cranes or heavy lili cranes IP address Special Notes. API publications necessarily address problems of a general nature. With respect to particular circumstances, local API Spec 2C is not intended to be used for the design, Elbricalion, and lesling of davits and/or emergency escape devices. This document specifies requirements and gives recommendations for the performance, dimensional and functional interchangeability, design, materials, testing, inspection, Latest Updates. AUXILIARY HOOK -MAX We would like to show you a description here but the site won't allow more API RP documents a quantitative approach to implementing RBI. Its methodology involves a rigorous quantitative assessment of the PoF (Probability of Failure) and the CoF (Consequence of Failure) associated with each equipment item in a particular process unit The Equity Engineering Group, Inc.'s software is the only API-branded RBI software IP address Special Notes. MAXIMUM ROPE SIZE 3/4" SHEAVE DIAMETER" MAXIMUM LINE FALLS WINCH MOUNTING On boom eliminates two blocking by luffing down; frees k space. API Monogram & API QR: Latest Updates.